

View Online at <https://aerobasegroup.com/nsn/5320-01-629-1792>

Fastener Length:

Between 1.323 inches and 1.343 inches

Head Style:

Straight pan

Head Height:

Between 0.077 inches and 0.090 inches

Width Between Flats:

0.093 inches

Shank Diameter:

Between 0.2410 inches and 0.2440 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.933 inches and 0.943 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.