## NSN 5320-01-629-5528



Pin-rivet Collar - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-629-5528 **Thread Class:** 3b **Thread Direction:** Right-hand **Identification Code Color:** Brown **Collar Outside Diameter:** Between 0.283 inches and 0.287 inches Collarheight: Between 0.405 inches and 0.425 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Collar Inside Diameter:** Between 0.169 inches and 0.173 inches **End Application:** 1680-01-628-7331 Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1640 inches **Collar Style:** Threaded (break off) type **Product Name:** Hi-lite stainless steel collar **Special Features:** Collar has solid film lube and washer has cetyl alcohol lube; torque-off inch to pounds is 15-25; uts lbs. is 2300 Material: Titanium washer **Material Specification:** Astm a493 assn standard 1st material response or qq-s-763 federal specification 2nd material response or ams 5686 national specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a58 (ams5640) assn standard 4th material response body **Surface Treatment Specification:** High shear specification 306, type i, color brown mfr ref single treatment response washer **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A530g0

No

**Demilitarization:**