

View Online at <https://aerobasegroup.com/nsn/5320-01-629-7694>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.020 inches

**Head Style:**

Crown countersunk less than 135 degrees

**Head Height:**

Between 0.796 inches and 0.822 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2410 inches and 0.2440 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.054 inches and 0.066 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17a

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-riquet, threaded, 100 deg, fl crown rivet hd

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4967 assn standard single material response or ams4928 assn standard single material response

**Surface Treatment:**

Aluminum alloy and chromate

**Surface Treatment Specification:**

Dps 4.50-197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0