

View Online at <https://aerobasegroup.com/nsn/5320-01-629-7694>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.020 inches

Head Style:

Crown countersunk less than 135 degrees

Head Height:

Between 0.796 inches and 0.822 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2410 inches and 0.2440 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.054 inches and 0.066 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

28

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded, 100 deg, fl crown rivet hd

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Surface Treatment:

Aluminum alloy and chromate

Surface Treatment Specification:

Dps 4.50-197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0