

View Online at <https://aerobasegroup.com/nsn/5320-01-641-6175>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.635 inches and 0.655 inches

**Head Style:**

Crown countersunk less than 135 degrees

**Head Height:**

Between 0.062 inches and 0.064 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2646 inches and 0.2651 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.450 inches and 0.494 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17 globemaster iii

**Grip Length:**

Between 0.245 inches and 0.255 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.2500 inches

**Countersink Angle:**

130.0 degrees

**Product Name:**

Pin-riquet, threaded-130 degrees flush crown hd, titanium

**Special Features:**

Featgmate with 3d0141 collars

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4967 federal specification single material response or ams 4928 federal specification single material response

**Surface Treatment Specification:**

Ams 2486 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0