

View Online at <https://aerobasegroup.com/nsn/5320-01-642-0581>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.285 inches and 1.305 inches

**Head Style:**

Crown countersunk less than 135 degrees

**Head Height:**

Between 0.0759 inches and 0.0780 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Stump

**Head Major Diameter:**

Between 0.5540 inches and 0.5604 inches

**Lubrication:**

Solid film and cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.750 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3750 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-rivet, threaded, shear, 100 degrees c'sunk head, hex point drive

**Material:**

Stainless steel

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams 2700 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0