NSN 5320-01-643-3620

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-643-3620 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.0725 inches and 1.0925 inches **Head Style:** Straight pan **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2641 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** B1-bacft **Grip Length:** Between 0.6825 inches and 0.6925 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Shear Strength:** 10490 double pounds per square inch **Product Name:** Hi-lok pin Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-643-3620

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0