

View Online at <https://aerobasegroup.com/nsn/5320-01-643-7785>

Thread Direction:

Right-hand

Fastener Length:

1.562 inches

Head Style:

Crown countersunk less than 135 degrees

Head Height:

Between 0.1027 inches and 0.1048 inches

Width Between Flats:

Between 0.160 inches and 0.180 inches

Shank Diameter:

Between 0.3271 inches and 0.3275 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.542 inches and 0.555 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a globemaster iii

Grip Length:

Between 0.495 inches and 0.505 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.3125 inches

Countersink Angle:

100.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-I-87132 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-I-87132 spec.