NSN 5320-01-645-1873

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-645-1873 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Green **Fastener Length:** Between 0.3605 inches and 0.3805 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3765 inches and 0.3813 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** B-52 **Grip Length:** Between 0.0395 inches and 0.0515 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Product Name:** Hi-lok pin Material: Stainless steel washer **Material Specification:** Ams5737 assn standard single material response or ams5731 assn standard single material response washer **Surface Treatment:** Cadmium washer **Surface Treatment Specification:**

Ams-qq-p-416, type ii, cl-2 assn standard single treatment response washer

Unjf

Thread Series Designator:

NSN 5320-01-645-1873

Pin-rivet - Page 2 of 2



| _ | | | | | | |
|---|----|----|---|----|---|---|
| C | he | 14 | | iŧ | 0 | • |
| J | | | _ | | ㄷ | - |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0