## NSN 5320-01-645-2085

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-645-2085 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Green **Fastener Length:** Between 0.5995 inches and 0.6015 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5018 inches and 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** B-52 **Grip Length:** Between 0.3025 inches and 0.3225 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Product Name:** Hi-lok pin Material: Stainless steel washer **Material Specification:** Ams5737 assn standard single material response or ams5731 assn standard single material response washer **Surface Treatment:** Cadmium washer **Surface Treatment Specification:** 

**Thread Series Designator:** 

Ams-qq-p-416, type ii, cl-2 assn standard single treatment response washer

Unjf

## NSN 5320-01-645-2085

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0