

View Online at <https://aerobasegroup.com/nsn/5320-01-645-3660>

**Thread Class:**

3a

**Fastener Length:**

0.513 inches

**Head Style:**

Cooper's

**Head Height:**

Between 0.079 inches and 0.081 inches

**Width Between Flats:**

Between 0.080 inches and 0.081 inches

**Shank Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.377 inches and 0.381 inches

**Grip Length:**

0.188 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

5820 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

9300 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Stainless steel

**Material Specification:**

Ams5737 federal specification single material response or ams5731 federal specification single material response

**Surface Treatment:**

Cadmium and passivate

**Surface Treatment Specification:**

Ams-qq-p-416 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0