NSN 5320-01-645-3682

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-645-3682

Thread Class	
3a	
Fastener Len	gth:
0.645 inches	
Head Style:	
Straight pan	
Head Height:	
Between 0.07	7 inches and 0.090 inches
Width Betwe	en Flats:
Between 0.09	5 inches and 0.097 inches
Shank Diame	eter:
Between 0.24	9 inches and 0.250 inches
Shank Style:	
Pin-rivet, stra	ight, threaded
Head Major [Diameter:
Between 0.41	5 inches and 0.440 inches
Grip Length:	
0.250 inches	
Thready Qty	Per Inch (tpi):
28	
Min. Tensile	Strength (psi):
5820 pounds	per square inch
Shear Streng	th:
9300 double p	bounds per square inch
Special Feat	ires:
Modified threa	ad
Material:	
Stainless stee	4
Material Spe	cification:
Ams5737 fed	eral specification single material response or ams5731 federal specification single material response
Surface Trea	tment:
Cadmium and	d passivate
Surface Trea	tment Specification:
Ams-qq-p-416	6 federal specification single treatment response
Thread Serie	s Designator:
Unjf	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizat	on:
No	

NSN 5320-01-645-3682

Pin-rivet - Page 2 of 2

Fiig: A528u0

