

View Online at <https://aerobasegroup.com/nsn/5320-01-645-8426>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.5925 inches and 2.6125 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

0.1875 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 2.5975 inches and 2.6075 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.1900 inches

**Product Name:**

Bolt, protruding head, hex drive

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Bms10-85, type 1, class (hi-kote 1, incotec 8g or kal-gard 2242 only) mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0