NSN 5320-01-645-9508



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-645-9508 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.513 inches **Head Style:** Crown countersunk less than 135 degrees **Head Height:** Between 0.0712 inches and 0.0783 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2028 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.334 inches and 0.347 inches Lubrication: Cetyl alcohol **End Application:** C-17a aircraft **Grip Length:** 0.188 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded, 100 degrees fl crown rivet hd **Special Features:** Finish per dps 4.50-197 (hi-kote 1 only) Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 federal specification single material response or ams 4928 federal specification single material response **Surface Treatment:** Aluminum and chromate

Unjf

Thread Series Designator:

NSN 5320-01-645-9508

Pin-rivet - Page 2 of 2



	L -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0