

View Online at <https://aerobasegroup.com/nsn/5320-01-645-9508>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.513 inches

Head Style:

Crown countersunk less than 135 degrees

Head Height:

Between 0.0712 inches and 0.0783 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2021 inches and 0.2028 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.334 inches and 0.347 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a aircraft

Grip Length:

0.188 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.1900 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded, 100 degrees fl crown rivet hd

Special Features:

Finish per dps 4.50-197 (hi-kote 1 only)

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 federal specification single material response or ams 4928 federal specification single material response

Surface Treatment:

Aluminum and chromate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0