
# NSN 5320-01-646-7548

Pin-rivet - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.285 inches and 1.305 inches

# Head Style:

Straight pan

# **Head Height:**

Between 0.130 inches and 0.140 inches

## Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.530 inches and 0.600 inches

Lubrication:

Cetyl alcohol

# **End Application:**

V-22 aircraft

# Grip Length:

0.875 inches

# Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

14000 pounds per square inch

# Thread Size:

0.375 inches

### Shear Strength:

21000 double pounds per square inch

#### **Product Name:**

Bolt, protuding head, hex drive

#### Material:

Titanium alloy

### **Material Specification:**

Ams4928orams4967 assn standard single material response

### Surface Treatment:

Aluminum

### **Surface Treatment Specification:**

Bms 10-85 mfr ref single treatment response

# NSN 5320-01-646-7548

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

