

View Online at <https://aerobasegroup.com/nsn/5320-01-647-5462>

**Fastener Length:**

Between 0.615 inches and 0.635 inches

**Head Style:**

Undersized oval countersunk

**Head Height:**

Between 0.003 inches and 0.005 inches

**Shank Diameter:**

Between 0.124 inches and 0.127 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Minor Diameter:**

0.1742 inches

**Countersink Height:**

0.0286 inches

**Chamfer Length:**

Between 0.029 inches and 0.049 inches

**End Application:**

An/apg-8 (v)

**Countersink Angle:**

100.0 degrees

**Product Name:**

Rivet, solid, 100 degree flush shear head, aluminum alloy, titanium columbian alloy

**Heat Treatment:**

H-32 strain hardened

**Material:**

Aluminum alloy 5056

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type ii, class 1, clear military specification single treatment response

**Specification Data:**

80205-nas1097 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.