NSN 5320-01-647-5462

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-647-5462

| Fastener Length: |
|--|
| Between 0.615 inches and 0.635 inches |
| Head Style: |
| Undersized oval countersunk |
| Head Height: |
| Between 0.003 inches and 0.005 inches |
| Shank Diameter: |
| Between 0.124 inches and 0.127 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Minor Diameter: |
| 0.1742 inches |
| Countersink Height: |
| 0.0286 inches |
| Chamfer Length: |
| Between 0.029 inches and 0.049 inches |
| End Application: |
| An/apg-8 (v) |
| Countersink Angle: |
| 100.0 degrees |
| Product Name: |
| Rivet, solid, 100 degree flush shear head, aluminum alloy, titanium columbian alloy |
| Heat Treatment: |
| H-32 strain hardened |
| Material: |
| Aluminum alloy 5056 |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type ii, class 1, clear military specification single treatment response |
| Specification Data: |
| 80205-nas1097 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No. |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| (|

Mil-a-8625 spec.