NSN 5320-01-647-5462

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-647-5462

Fastener Length:
Between 0.615 inches and 0.635 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Minor Diameter:
0.1742 inches
Countersink Height:
0.0286 inches
Chamfer Length:
Between 0.029 inches and 0.049 inches
End Application:
An/apg-8 (v)
Countersink Angle:
100.0 degrees
Product Name:
Rivet, solid, 100 degree flush shear head, aluminum alloy, titanium columbian alloy
Heat Treatment:
H-32 strain hardened
Material:
Aluminum alloy 5056
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type ii, class 1, clear military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No.
Fiig:
A040a0
Mil-std (military Standard):
(

Mil-a-8625 spec.