

View Online at <https://aerobasegroup.com/nsn/5320-01-647-5746>

**Identification Code Color:**

Green

**Fastener Length:**

0.717 inches

**Head Style:**

Countersunk w/protruding stud

**Head Height:**

Between 0.062 inches and 0.070 inches

**Shank Diameter:**

0.195 inches

**Shank Style:**

Pin-rivet, multiple grooved

**Head Major Diameter:**

Between 0.250 inches and 0.272 inches

**End Application:**

An/apg-8 (v)

**Grip Length:**

Between 0.531 inches and 0.595 inches

**Hardness Rating:**

48.0 rockwell c and 53.0 rockwell c body

**Shear Strength:**

2340 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Fastener, blind, high strength, pull type, positive mechanical lock, protruding head, alloy steel, 112 ksi ftu

**Special Features:**

No lubrication except mfg option to lubricate lock mechanism with lox compatible dry film lube; u05 fastener can be installed with a single or double action tool, see nasm81177 appendix a for tool selection chart

**Material:**

Steel sleeve

**Material Specification:**

Astm a108 assn standard single material response sleeve

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-dtl-83488 military specification single treatment response

**Specification Data:**

80205-nas-90354 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-dtl-83488 spec.