

View Online at <https://aerobasegroup.com/nsn/5320-01-647-5746>

Identification Code Color:

Green

Fastener Length:

0.717 inches

Head Style:

Countersunk w/protruding stud

Head Height:

Between 0.062 inches and 0.070 inches

Shank Diameter:

0.195 inches

Shank Style:

Pin-rivet, multiple grooved

Head Major Diameter:

Between 0.250 inches and 0.272 inches

End Application:

An/apg-8 (v)

Grip Length:

Between 0.531 inches and 0.595 inches

Hardness Rating:

48.0 rockwell c and 53.0 rockwell c body

Shear Strength:

2340 single pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Fastener, blind, high strength, pull type, positive mechanical lock, protruding head, alloy steel, 112 ksi ftu

Special Features:

No lubrication except mfg option to lubricate lock mechanism with lox compatible dry film lube; u05 fastener can be installed with a single or double action tool, see nasm81177 appendix a for tool selection chart

Material:

Steel sleeve

Material Specification:

Astm a108 assn standard single material response sleeve

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-dtl-83488 military specification single treatment response

Specification Data:

80205-nas-90354 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-dtl-83488 spec.