

View Online at <https://aerobasegroup.com/nsn/5320-01-648-2694>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.615 inches and 0.635 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.102 inches and 0.112 inches

**Width Between Flats:**

Between 0.127 inches and 0.129 inches

**Shank Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**End Application:**

An/apg-8 (v) (

**Grip Length:**

Between 0.120 inches and 0.130 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.312 inches

**Countersink Angle:**

Between 90.0 degrees and 100.0 degrees

**Product Name:**

Pin, riquet, threaded, tension protruding head, hex point drive

**Material:**

Titanium alloy uns r56400

**Surface Treatment:**

Anodize

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0