

View Online at <https://aerobasegroup.com/nsn/5320-01-648-5275>

**Fastener Length:**

0.405 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.333 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film

**End Application:**

C5m fuselage

**Grip Length:**

Between 0.219 inches and 0.282 inches

**Min. Tensile Strength (psi):**

1350 pounds per square inch

**Hardness Rating:**

326.0 knoop and 466.0 knoop sleeve

**Shear Strength:**

2340 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Fastener, blind, high strength, pull type, positive mechanical lock, 100 degree flush head, alloy steel, 112 ksi fsu

**Material:**

Steel stem

**Material Specification:**

Astm a 108 assn standard single material response stem

**Surface Treatment:**

Cadmium or passivate or aluminum mechanical lock

**Surface Treatment Specification:**

Ams-qq-p-416, type ii, class (carbon and alloy steel) national standard 1st treatment response or ams2700, method 1, class 4(a286 and type 316 cres) national standard 2nd treatment response or mil-dtl-83488 government std/spec 3rd treatment response mechanical lock

**Specification Data:**

80205-nas-90353 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0