

View Online at <https://aerobasegroup.com/nsn/5320-01-648-5275>

Fastener Length:

0.405 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.333 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

End Application:

C5m fuselage

Grip Length:

Between 0.219 inches and 0.282 inches

Min. Tensile Strength (psi):

1350 pounds per square inch

Hardness Rating:

326.0 knoop and 466.0 knoop sleeve

Shear Strength:

2340 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Fastener, blind, high strength, pull type, positive mechanical lock, 100 degree flush head, alloy steel, 112 ksi fsu

Material:

Steel stem

Material Specification:

Astm a 108 assn standard single material response stem

Surface Treatment:

Cadmium or passivate or aluminum mechanical lock

Surface Treatment Specification:

Ams-qq-p-416, type ii, class (carbon and alloy steel) national standard 1st treatment response or ams2700, method 1, class 4(a286 and type 316 cres) national standard 2nd treatment response or mil-dtl-83488 government std/spec 3rd treatment response mechanical lock

Specification Data:

80205-nas-90353 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0