

View Online at <https://aerobasegroup.com/nsn/5320-01-649-4789>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.697 inches and 0.717 inches

**Head Style:**

Crown countersunk less than 135 degrees

**Head Height:**

Between 0.0560 inches and 0.0760 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2802 inches and 0.2807 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.481 inches and 0.526 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17 globemaster iii

**Grip Length:**

Between 0.390 inches and 0.400 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.2500 inches

**Countersink Angle:**

130.0 degrees

**Product Name:**

Pin-rivet, threaded, 130 degrees flush crown head, titanium

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4967 assn standard single material response or ams4928 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Ams 2486 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0