

View Online at <https://aerobasegroup.com/nsn/5320-01-649-4789>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.697 inches and 0.717 inches

Head Style:

Crown countersunk less than 135 degrees

Head Height:

Between 0.0560 inches and 0.0760 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2802 inches and 0.2807 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.481 inches and 0.526 inches

Lubrication:

Cetyl alcohol

End Application:

C-17 globemaster iii

Grip Length:

Between 0.390 inches and 0.400 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

95000 pounds per square inch

Thread Size:

0.2500 inches

Countersink Angle:

130.0 degrees

Product Name:

Pin-rivet, threaded, 130 degrees flush crown head, titanium

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Ams 2486 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0