NSN 5320-01-650-1706



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-650-1706 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color: Bronze Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.5554 inches and 0.5604 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.822 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Flush shear head Material: Steel comp 4340 **Material Specification:** Mil-s-5000 military standard 1st material response or mil-s-5626 military standard 2nd material response or mil-s-6049 military standard 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal standard all treatment responses

Thread Series Designator:

Unjf

NSN 5320-01-650-1706

Pin-rivet - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A528u0	

Shelf Life:

Mil-std (military Standard):

Mil-s-5000 spec.