## NSN 5320-01-653-8780

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-653-8780

| Fastener Length:  |
|---|
| Between 0.6775 inches and 0.6975 inches   |
| Head Style:   |
| Universal   |
| Head Height:  |
| Between 0.080 inches and 0.090 inches   |
| Shank Diameter:   |
| Between 0.1865 inches and 0.1905 inches   |
| Shank Style:  |
| Straight w/radius chamfered tip   |
| Head Major Diameter:  |
| Between 0.356 inches and 0.394 inches   |
| End Application:  |
| C-130j large aircraft infrared counter measures   |
| Product Name:   |
| Rivet, solid, universal head, aluminum alloy and titanium columbium alloy   |
| Special Features:   |
| Material identification to be marked on head; 5056 material will be indicated with a cross, raised and 0.030 maximum size |
| Heat Treatment:   |
| H-32 strain hardened  |
| Material:   |
| Aluminum alloy 5056   |
| Material Specification:   |
| Qq-a-430 federal specification single material response   |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mil-a-8625, ty ii, cl 2 military specification single treatment response  |
| Specification Data:   |
| 80205-nas-20470 professional/industrial association standard  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A040a0  |
| Mil-std (military Standard):  |
| Mil-a-8625 spec.  |