## NSN 5320-01-653-9521



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-653-9521 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.440 inches and 1.460 inches **Head Style:** Crown coutersunk greater than 135 degrees **Head Height:** Between 0.045 inches and 0.047 inches Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.297 inches and 0.302 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** Various c5 **Grip Length:** 1.125 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Product Name:** Hi-lok hi-tigue pin Material: Nickel alloy 718 **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-653-9521

Pin-rivet - Page 2 of 2



| Dem |  |  |  |
|-----|--|--|--|
|     |  |  |  |
|     |  |  |  |

No

Fiig:

A528u0