## NSN 5320-01-654-0753

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-654-0753 **Thread Class:** 31 **Thread Direction:** Right-hand Fastener Length: Between 0.482 inches and 0.502 inches **Head Style:** Flush countersunk Width Between Flats: 0.112 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.350 inches **End Application:** F-22 **Grip Length:** Between 0.183 inches and 0.193 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 7060 double pounds per square inch **Countersink Angle:** Between 99.3 degrees and 100.3 degrees **Special Features:** S indicates spline lock recess Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5320-01-654-0753

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0