## NSN 5320-01-655-8000



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-655-8000 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.312 inches **Head Style:** Crown countersunk less than 135 degrees **Head Height:** Between 0.685 inches and 0.710 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.454 inches and 0.467 inches Lubrication: Cetyl alcohol **End Application:** C-17a aircraft **Grip Length:** 0.812 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded, 100 degrees fl crown shear hd, titanium Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Surface Treatment Specification:** Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-655-8000

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0