

View Online at <https://aerobasegroup.com/nsn/5325-00-130-5824>

**Cross Sectional Shape:**

Double oval

**Inside Diameter:**

Between 1.408 inches and 1.423 inches

**Casehardening Indicator:**

Not casehardened

**Outside Diameter:**

Between 1.614 inches and 1.629 inches

**Major Thickness:**

Between 0.048 inches and 0.052 inches

**Ring Style:**

Spiral

**Usage Design:**

External

**Material Hardness Rating:**

Between 39.8 rockwell c and 48.5 rockwell c

**Strength Rating:**

185000.0 pounds per square inch tensile

**Material:**

Steel, ams 5519 or steel, mil-s-5059, type 302 or steel, qq-s-766, class 302 or steel, federal standard 66, aisi 302/sae 30302

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302 or steel comp 302

**Material Specification:**

Ams 5519 assn standard 1st material response and mil-s-5059, type 302 military specification 2nd material response and qq-s-766, class 302 federal specification 3rd material response and federal standard 66 federal standard 4th material response or aisi 302 assn standard single material response or sae 30302 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated, qq-p-35

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-g

**Mil-std (military Standard):**

Mil-s-5059 spec.