

View Online at <https://aerobasegroup.com/nsn/5325-00-155-5278>

Diameter:

0.344 inches

Securing Device Type:

Spring

End Application:

W/s: kidd class ddg; support equipment, b-52 aircraft; ticonderoga class cg (47); oliver perry class ffg; defense meteorological satellite program (dmsp); low altitude navigation & targeting infrared system (lantirn); meteorological and weather network 433l: spruance class dd (963); communications terminal satellite an/gsc-3 (v) 1

Turnlock Stud Head Style:

Knurled

Stud Assembly Style:

Stud assembly

Distance From Engaging Member To Largest Bearing Surface Of Head:

0.609 inches

Eyelet Outside Diameter:

0.344 inches

Eyelet Length:

0.341 inches

Material Accommodated Thickness:

0.060 inches

Drive Type:

Knurled or slotted

Stud Thread Size And Series/type Designator:

0.138-32 unjc

Stud Head Height:

Between 0.070 inches and 0.075 inches

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303pb or steel comp 303se or steel comp 304 or steel comp 305 or steel comp 316

Surface Treatment:

Passivate stud

Surface Treatment Specification:

Qq-p-35, type 1 federal specification single treatment response stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A05400