

View Online at <https://aerobasegroup.com/nsn/5325-00-197-3359>

Grip Length:

0.700 inches

Diameter:

0.500 inches

Center To Center Distance Between Mounting Holes:

Between 0.873 inches and 0.877 inches

Mounting Style:

Plain w/mounting hole

Turnlock Stud Shank Style:

Stud shank

Turnlock Stud Head Style:

Flat fillister

Turnlock Receptacle Style:

Receptacle

Receptaclelength:

1.135 inches

Receptacle Height:

0.625 inches

Receptacle Width:

0.625 inches

Material Accommodated Thickness:

Between 0.256 inches and 0.325 inches

Drive Type:

Cross recess

Stud Head Height:

0.125 inches

Stud Shank Major Diameter:

Between 0.373 inches and 0.375 inches

Turnlock Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1055 or steel comp 1060 or steel comp 1095

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 3 federal specification single treatment response

Specification Or Standard:

2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A05400