NSN 5325-00-205-6701

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-00-205-6701

Double oval Inside Diameter: 3.260 inches Casehardening Indicator: Not casehardened Outside Diameter: 3.636 inches Major Thickness: 0.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 21100.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g	Cross Sectional Shape:
3.260 inches Casehardening Indicator: Not casehardened Outside Diameter: 3.636 inches Major Thickness: 0.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Double oval
Casehardening Indicator: Not casehardened Outside Diameter: 3.636 inches Major Thickness: 0.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inside Diameter:
Not casehardened Outside Diameter: 3.636 inches Major Thickness: 0.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.260 inches
Outside Diameter: 3.636 inches Major Thickness: 0.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Casehardening Indicator:
Major Thickness: 0.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not casehardened
Major Thickness: 0.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Outside Diameter:
O.059 inches Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.636 inches
Ring Style: Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Major Thickness:
Spiral Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.059 inches
Usage Design: Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ring Style:
Internal Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Spiral
Material Hardness Rating: Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Usage Design:
Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Internal
Strength Rating: 211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Hardness Rating:
211000.0 pounds per square inch tensile Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 64.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n
Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Strength Rating:
Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	211000.0 pounds per square inch tensile
Material: Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090
Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel, fed, qq-s-633, composition fs1070, fs1074, fs1080, fs1085 or 1090
Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium plated
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
_	No
T252-g	Fiig:
	T252-g