

View Online at <https://aerobasegroup.com/nsn/5325-00-278-0734>

**Grip Length:**

0.375 inches

**Diameter:**

0.500 inches

**Center To Center Distance Between Mounting Holes:**

Between 0.873 inches and 0.877 inches

**Mounting Style:**

Plain w/mounting hole

**Turnlock Stud Shank Style:**

Stud shank

**Turnlock Stud Head Style:**

Flat fillister

**Turnlock Receptacle Style:**

Receptacle

**Receptaclelength:**

1.135 inches

**Receptacle Height:**

0.625 inches

**Receptacle Width:**

0.625 inches

**Material Accommodated Thickness:**

Between 0.116 inches and 0.185 inches

**Drive Type:**

Cross recess

**Stud Head Height:**

0.125 inches

**Stud Shank Major Diameter:**

Between 0.373 inches and 0.375 inches

**Turnlock Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Material:**

Steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1055 or steel comp 1060 or steel comp 1095

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 class 3 federal specification single treatment response

**Specification Or Standard:**

2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A05400