

View Online at <https://aerobasegroup.com/nsn/5325-00-406-5364>

**Diameter:**

0.420 inches

**Securing Device Type:**

Washer

**Turnlock Stud Head Style:**

Flat fillister

**Stud Assembly Style:**

Stud assembly

**Distance From Engaging Member To Largest Bearing Surface Of Head:**

1.120 inches

**Eyelet Outside Diameter:**

0.258 inches

**Eyelet Length:**

0.385 inches

**Material Accommodated Thickness:**

Between 0.438 inches and 0.562 inches

**Drive Type:**

Slotted

**Stud Thread Size And Series/type Designator:**

0.164-32 unc

**Stud Head Height:**

0.495 inches

**Material:**

Steel comp 304 stud or steel comp 305 stud or steel comp 302 stud or steel comp 316 stud or steel comp 303 stud

**Material Specification:**

Mil-s-5059 military specification single material response washer

**Surface Treatment:**

Passivate washer

**Surface Treatment Specification:**

Mil-std-171, finish no. 5.4.1 military standard single treatment response washer

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A05400

**Mil-std (military Standard):**

Mil-s-5059 spec.