NSN 5325-00-478-0512

Turnlock Fastener Receptacle - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-00-478-0512

| Center To Center Distance Between Mounting Holes: |
|---|
| Between 0.998 inches and 1.002 inches |
| Mounting Style: |
| Plain w/mounting hole |
| Turnlock Receptacle Style: |
| Receptacle |
| Receptaclelength: |
| 1.295 inches |
| Receptacle Height: |
| 0.834 inches |
| Receptacle Width: |
| 0.600 inches |
| Receptacle Thread Size And Series/type Designator: |
| 0.250-28 unf |
| Turnlock Mounting Hole Diameter: |
| Between 0.130 inches and 0.135 inches |
| Special Features: |
| Double lead thread, stud protrusion 0.000 in. Nom |
| Material: |
| Steel comp 8740 stud |
| Material Specification: |
| Ams 6322 assn standard single material response stud |
| Surface Treatment: |
| Cadmium retainer and chromate retainer |
| Surface Treatment Specification: |
| Qq-p-416, type 2 cl2 federal specification single treatment response barrel |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A05400 |
| |