## NSN 5325-00-584-9930

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-00-584-9930

Rectangular  Casehardening Indicator: Not casehardened  Outside Diameter: Between 4.092 inches and 4.222 inches  Major Thickness: Between 0.106 inches and 0.112 inches  Ring Style: Internal  Usage Design: Internal  Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c  Material: Steel, ams 5520  Material: Steel comp 632  Material Specification: Ams 5520 assn standard single material response  Surface Treatment: Passivate  Surface Treatment: Passivated, qq-p-35  Shelf Life: N/a  Unit Of Measure: Demilitarization: No
Not casehardened  Outside Diameter:  Between 4.092 inches and 4.222 inches  Major Thickness:  Between 0.106 inches and 0.112 inches  Ring Style: Internal  Usage Design: Internal  Material Hardness Rating:  Between 44.0 rockwell c and 51.0 rockwell c  Material:  Steel, ams 5520  Material:  Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Outside Diameter: Between 4.092 inches and 4.222 inches Major Thickness: Between 0.106 inches and 0.112 inches Ring Style: Internal Usage Design: Internal Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c Material: Steel, ams 5520 Material: Steel comp 632 Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Between 4.092 inches and 4.222 inches  Major Thickness: Between 0.106 inches and 0.112 inches  Ring Style: Internal  Usage Design: Internal  Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c  Material: Steel, ams 5520  Material: Steel comp 632  Material Specification: Ams 5520 assn standard single material response  Surface Treatment: Passivate  Surface Treatment: Passivated, qq-p-35  Shelf Life: N/a  Unit Of Measure: Demilitarization:
Major Thickness: Between 0.106 inches and 0.112 inches Ring Style: Internal Usage Design: Internal Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c Material: Steel, ams 5520 Material: Steel comp 632 Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Between 0.106 inches and 0.112 inches  Ring Style: Internal Usage Design: Internal Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c Material: Steel, ams 5520 Material: Steel comp 632 Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Ring Style: Internal Usage Design: Internal Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c Material: Steel, ams 5520 Material: Steel comp 632 Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Internal Usage Design: Internal Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c Material: Steel, ams 5520 Material: Steel comp 632 Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Usage Design: Internal Material Hardness Rating: Between 44.0 rockwell c and 51.0 rockwell c Material: Steel, ams 5520 Material: Steel comp 632 Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Internal  Material Hardness Rating:  Between 44.0 rockwell c and 51.0 rockwell c  Material:  Steel, ams 5520  Material:  Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Material Hardness Rating:  Between 44.0 rockwell c and 51.0 rockwell c  Material:  Steel, ams 5520  Material:  Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Between 44.0 rockwell c and 51.0 rockwell c  Material: Steel, ams 5520  Material: Steel comp 632  Material Specification: Ams 5520 assn standard single material response  Surface Treatment: Passivate  Surface Treatment: Passivated, qq-p-35  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
Material: Steel, ams 5520  Material: Steel comp 632  Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel, ams 5520  Material: Steel comp 632  Material Specification: Ams 5520 assn standard single material response  Surface Treatment: Passivate  Surface Treatment: Passivated, qq-p-35  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
Material: Steel comp 632 Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel comp 632  Material Specification: Ams 5520 assn standard single material response  Surface Treatment: Passivate  Surface Treatment: Passivated, qq-p-35  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
Material Specification: Ams 5520 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Surface Treatment:  Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Passivate  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Surface Treatment: Passivated, qq-p-35 Shelf Life: N/a Unit Of Measure: Demilitarization:
Passivated, qq-p-35  Shelf Life: N/a Unit Of Measure: Demilitarization:
Shelf Life: N/a Unit Of Measure: Demilitarization:
N/a Unit Of Measure: Demilitarization:
Unit Of Measure: Demilitarization:
Demilitarization:
No
Fiig:
T252-g