## NSN 5325-00-735-8061

Turnlock Fastener Stud - Page 1 of 1



Grip Length:0.450 inchesDiameter:0.495 inchesSecuring Device Type:RingTurnlock Stud Head Style:Flat fillisterMaterial Accommodated Thickness:Between 0.188 inches and 0.250 inchesDrive Type:SocketStud Head Height:0.125 inchesStud Shank Major Diameter:0.374 inchesMaterial Specification:Ams 6322 assn standard single material responseSurface TreatmentQarp-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aTime Comperation:N/aSurface Treatment Specification single treatment responseSurface Treatment Sp	View Online at https://aerobasegroup.com/nsn/5325-00-735-8061
Diameter:0.495 inchesSecuring Device Type:RingTurnlock Stud Head Style:Flat fillisterMaterial Accommodated Thickness:Between 0.188 inches and 0.250 inchesDrive Type:SocketStud Head Height:0.125 inchesStud Shank Major Diameter:0.374 inchesMaterialSteel comp 8740Material Specification:Cadmium and chromateSurface TreatmentCadmium and chromateSurface Treatment Specification single treatment responseShelf Life:N/aN/aDint Of Measure:-Demilitarization:No	Grip Length:
0.495 inches Securing Device Type: Ring Turnlock Stud Head Style: Flat fillister Material Accommodated Thickness: Between 0.188 inches and 0.250 inches Drive Type: Socket Stud Head Height: 0.125 inches Stud Head Height: 0.125 inches Stud Shank Major Diameter: 0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qa-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0.450 inches
Securing Device Type: Ring Turnlock Stud Head Style: Flat fillister Material Accommodated Thickness: Between 0.188 inches and 0.250 inches Drive Type: Socket Drive Type: Socket Stud Head Height: 0.125 inches Stud Shank Major Diameter: 0.374 inches Stud Shank Major Diameter: 0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Diameter:
Ring         Turnlock Stud Head Style:         Flat fillister         Material Accommodated Thickness:         Between 0.188 inches and 0.250 inches         Drive Type:         Socket         Stud Head Height:         0.125 inches         Stud Shank Major Diameter:         0.374 inches         Material:         Steel comp 8740         Material Specification:         Ams 6322 assn standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification:         Qup-416, type 2, cl 3 federal specification single treatment response         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No	0.495 inches
Turnlock Stud Head Style:         Flat fillister         Material Accommodated Thickness:         Between 0.188 inches and 0.250 inches         Drive Type:         Socket         Stud Head Height:         0.125 inches         Stud Shank Major Diameter:         0.374 inches         Material:         Steel comp 8740         Material Specification:         Ams 6322 assn standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification:         Qa-p-416, type 2, cl 3 federal specification single treatment response         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No	Securing Device Type:
Flat fillisterMaterial Accommodated Thickness:Between 0.188 inches and 0.250 inchesDrive Type:SocketSocketStud Head Height:0.125 inchesStud Shank Major Diameter:0.374 inchesMaterial:Steel comp 8740Material Specification:Ams 6322 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qr.p-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aUnit Of Measure:-Demilitarization:No	Ring
Material Accommodated Thickness:Between 0.188 inches and 0.250 inchesDrive Type:SocketStud Head Height:0.125 inchesStud Shank Major Diameter:0.374 inchesMaterial:Steel comp 8740Material Specification:Ams 6322 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aUnit Of Measure:Demilitarization:No	Turnlock Stud Head Style:
Between 0.188 inches and 0.250 inches Drive Type: Socket Stud Head Height: 0.125 inches Stud Shank Major Diameter: 0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Flat fillister
Drive Type: Socket Stud Head Height: 0.125 inches Stud Shank Major Diameter: 0.374 inches Material: 0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Material Accommodated Thickness:
Socket Stud Head Height: 0.125 inches Stud Shank Major Diameter: 0.374 inches Material: O.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.188 inches and 0.250 inches
Stud Head Height: 0.125 inches Stud Shank Major Diameter: 0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Drive Type:
0.125 inches Stud Shank Major Diameter: 0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Socket
Stud Shank Major Diameter: 0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Stud Head Height:
0.374 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0.125 inches
Material:Steel comp 8740Material Specification:Ams 6322 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aUnit Of Measure:Demilitarization:No	Stud Shank Major Diameter:
Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0.374 inches
Material Specification:Ams 6322 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseShelf Life:N/aUnit Of Measure:Demilitarization:No	Material:
Ams 6322 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Steel comp 8740
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Material Specification:
Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Ams 6322 assn standard single material response
Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Surface Treatment:
Qq-p-416, type 2, cl 3 federal specification single treatment response Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Cadmium and chromate
Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Surface Treatment Specification:
N/a Unit Of Measure:  Demilitarization: No	Qq-p-416, type 2, cl 3 federal specification single treatment response
Unit Of Measure:  Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A05400	A05400