View Online at https://aerobasegroup.com/nsn/5325-00-803-7301

Cross Sectional Shape:

Rectangular

Inside Diameter:

Between 0.456 inches and 0.463 inches

Casehardening Indicator:

Not casehardened

Major Thickness:

Between 0.033 inches and 0.037 inches

Ring Style:

External

End Application:

W/s: aircraft, (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-1 aircraft, elevators, aircraft; boilers, 1200 psi; stream (std. Tensioned replensihment at sea method); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); fire pums; guided missile launching system, mk 26 (gmls); gun, 5-in./54 cal, mk-42 & 45

Usage Design:

External

Material Hardness Rating:

Between 66.0 rockwell superficial 30-n and 71.0 rockwell superficial 30-n

Material:

Steel, fed standard 66 aisi 1066 or 1069 or 1070 or 1072 or 1074 or 1075 or 1078 or 1080 or 1084 or 1086 or 1090

Material:

Steel, fed standard 66 aisi 1066 or 1069 or 1070 or 1072 or 1074 or 1075 or 1078 or 1080 or 1084 or 1086 or 1090

Surface Treatment:

Cadmium and chromate or chromate zinc

Surface Treatment:

Cadmium, qq-p-416, type 2, class 3 or zinc plated, mil-c-81562, type 2 cl 3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-g