Turnlock Fastener Stud Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-00-923-9522

| Diameter:  |
|--|
| 1.020 inches   |
| Turnlock Stud Head Style:  |
| Err-090  |
| Stud Assembly Style:   |
| Stud assembly  |
| Distance From Engaging Member To Largest Bearing Surface Of Head:  |
| Between 0.565 inches and 0.605 inches  |
| Eyelet Outside Diameter:   |
| Between 0.341 inches and 0.348 inches  |
| Eyelet Length:   |
| 0.322 inches   |
| Material Accommodated Thickness:   |
| Between 0.201 inches and 0.230 inches  |
| Stud Head Height:  |
| 0.620 inches   |
| Special Features:  |
| Knurled head   |
| Material:  |
| Steel comp 305 eyelet or steel comp 303 eyelet   |
| Material Specification:  |
| Qq-s-766 federal specification 1st material response eyelet or astma582 assn standard 2nd material response eyelet |
| Surface Treatment:   |
| Passivate  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A05400   |
|  |
|  |