NSN 5325-00-947-6242

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-00-947-6242

Cross Sectional Shape: Rectangular Inside Diameter: Between 1.121 inches and 1.129 inches Casehardening Indicator: Not casehardened Outside Diameter: 1.275 inches Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T252-g	
Inside Diameter: Between 1.121 inches and 1.129 inches Casehardening Indicator: Not casehardened Outside Diameter: 1.275 inches Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cross Sectional Shape:
Between 1.121 inches and 1.129 inches Casehardening Indicator: Not casehardened Outside Diameter: 1.275 inches Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rectangular
Casehardening Indicator: Not casehardened Outside Diameter: 1.275 inches Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inside Diameter:
Not casehardened Outside Diameter: 1.275 inches Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 1.121 inches and 1.129 inches
Outside Diameter: 1.275 inches Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Casehardening Indicator:
1.275 inches Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not casehardened
Major Thickness: Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Outside Diameter:
Between 0.060 inches and 0.061 inches Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.275 inches
Ring Style: Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Major Thickness:
Wire Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.060 inches and 0.061 inches
Usage Design: Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ring Style:
Internal Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire
Material Hardness Rating: Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Usage Design:
Between 47.0 rockwell c and 52.0 rockwell c Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Internal
Material: Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Hardness Rating:
Steel, ams, ams5121, composition 1095 Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 47.0 rockwell c and 52.0 rockwell c
Material: Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Steel, ams, ams5121, composition 1095 Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel, ams, ams5121, composition 1095
Surface Treatment: Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Cadmium Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel, ams, ams5121, composition 1095
Surface Treatment: Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Cadmium plated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium plated
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
_	No
T252-g	Fiig:
	T252-g