

View Online at <https://aerobasegroup.com/nsn/5325-00-982-2559>

Cross Sectional Shape:

Rectangular

Inside Diameter:

Between 0.256 inches and 0.266 inches

Casehardening Indicator:

Not casehardened

Outside Diameter:

0.390 inches

Major Thickness:

Between 0.029 inches and 0.033 inches

End Style:

Vertex below center

Ring Style:

Straight gap

Usage Design:

External

Material Hardness Rating:

Between 46.0 rockwell c and 52.0 rockwell c

Strength Rating:

150000.0 pounds per square inch yield

Material:

Steel, federal standard 66, comp 1008 or steel, federal standard 66, comp 1010 or steel, federal standard 66, comp 1012 or steel, federal standard 66, comp 1015 or steel, federal standard 66, comp 1016 or steel, federal standard 66, comp 1017 or steel, federal standard 66, comp 1018 or steel, federal standard 66, comp 1019

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019

Material Specification:

Fed standard 66, comp 1008 federal standard 1st material response and federal standard 66, comp 1010 federal standard 2nd material response and federal standard 66, comp 1012 federal standard 3rd material response and federal standard 66, comp 1015 federal standard 4th material response and federal standard 66, comp 1016 federal standard 5th material response and federal standard 66, comp 1017 federal standard 6th material response and federal standard 66, comp 1018 federal standard 7th material response and federal standard 66, comp 1019 federal standard 8th material response

Surface Treatment:

Zinc and chromate or zinc

Surface Treatment:

Zinc, astm b633, type 2 or zinc plated, mil-c-81562, type 2, class 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252.g