

View Online at <https://aerobasegroup.com/nsn/5325-01-026-3243>

Cross Sectional Shape:

Rectangular

Inside Diameter:

Between 0.206 inches and 0.214 inches

Casehardening Indicator:

Not casehardened

Major Thickness:

Between 0.023 inches and 0.027 inches

Ring Style:

C

Usage Design:

External

Material Hardness Rating:

Between 63.0 rockwell superficial 30-n and 69.5 rockwell superficial 30-n

Material:

Steel, ams 5520

Material:

Steel comp 632

Material Specification:

Ams 5520 assn standard single material response

Surface Treatment:

Passivate

Special Test Features:

Special quality control testing

Surface Treatment:

Passivated, qq-p-35

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

1 type and 6 class

Departure From Cited Document:

As modified by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-g