## NSN 5325-01-045-3573

**Countersink Angle In Deg:** 

Between 0.072 inches and 0.133 inches

Between 0.325 inches and 0.358 inches

Between 0.748 inches and 0.752 inches

100.0

**Grip Length:** 

Diameter:

Turnlock Fastener Assembly - Page 1 of 2

**Center To Center Distance Between Mounting Holes:** 



View Online at https://aerobasegroup.com/nsn/5325-01-045-3573

Mounting Style:
Countersunk
Securing Device Type:
Ring
Minor Diameter:
0.219 inches
Turnlock Stud Shank Style:
Stud shank
Extension Length:
0.361 inches
Turnlock Stud Head Style:
Flat countersunk
Turnlock Receptacle Style:
Receptacle
Receptaclelength:
1.012 inches
Receptacle Height:
0.332 inches
Receptacle Width:
0.410 inches
Material Accommodated Thickness:
Between 0.438 inches and 0.500 inches
Drive Type:
Torque set
Stud Thread Size And Series/type Designator:
0.8-32 unc
Stud Shank Major Diameter:
0.249 inches
Turnlock Mounting Hole Diameter:
Between 0.250 inches and 0.254 inches
Material:
Steel
Surface Treatment:
Cadmium

## NSN 5325-01-045-3573

Turnlock Fastener Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A05400