NSN 5325-01-115-6834

Retaining Ring - Page 1 of 1

T252-g



View Online at https://aerobasegroup.com/nsn/5325-01-115-6834

| Cross Sectional Shape: |
|--|
| Rounded outside corners |
| Inside Diameter: |
| Between 3.128 inches and 3.158 inches |
| Casehardening Indicator: |
| Not casehardened |
| Outside Diameter: |
| Between 3.504 inches and 3.534 inches |
| Major Thickness: |
| Between 0.037 inches and 0.041 inches |
| Ring Style: |
| Special |
| Usage Design: |
| Internal |
| Strength Rating: |
| 221000.0 pounds per square inch tensile |
| Material: |
| Steel, federal standard 66, comp 1070 or steel, federal standard 66, comp 1074 or steel, federal standard 66, comp 1078 or steel, |
| federal standard 66, comp 1080 or steel, federal standard 66, comp 1084 or steel, federal standard 66, comp 1086 or steel, federal |
| standard 66, comp 1090 |
| Material: |
| Steel comp 1070 or steel comp 1074 or steel comp 1078 or steel comp 1080 or steel comp 1070 or steel comp 1086 or steel comp 1090 |
| Material Specification: |
| Fed standard 66, comp 1070 federal standard 1st material response and federal standard 66, comp 1074 federal standard 2nd material |
| response and federal standard 66, comp 1078 federal standard 3rd material response and federal standard 66, comp 1080 federal standard |
| 4th material response and federal standard 66, comp 1084 federal standard 5th material response and federal standard 66, comp 1086 |
| federal standard 6th material response and federal standard 66, comp 1090 federal standard 7th material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Surface Treatment: |
| Cadmium, qq-p-416, type 2, class 2 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |