

View Online at <https://aerobasegroup.com/nsn/5325-01-123-0948>

Pinhole Diameter:

Between 0.524 inches and 0.539 inches

Fastener Style:

Lock pin

Length From Body Shoulder To Hole Center:

1.310 inches

Length From Body Hole Center To Body End:

0.500 inches

Stud Body Diameter:

1.508 inches

Fastener Stud Shank Length:

4.710 inches

Fastener Stud Shank Diameter:

1.000 inches

Special Features:

Heat treat to 150-170 ksi per mil-h-6875; apply mil-g-7711 grease or vv-p-236 petrolatum on all threaded surfaces; 0.124 inch diameter hole 0.118 inch from end of threads

Material:

Steel comp 4140

Material Specification:

Mil-s-5626, 4140 cond d military specification single material response

Surface Treatment:

Cadmium post and paint post

Surface Treatment Specification:

Qq-p-416, type 2 cd 1 federal specification 1st treatment response post and mil-p-23377 military specification 2nd treatment response post and mil-c-22751 military specification 3rd treatment response post and mil-c-83286 military specification 4th treatment response post and mil-c-16173, grade 1 military specification 5th treatment response post

Thread Size And Series/type Designator:

1.000-12 unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A05400

Mil-std (military Standard):

Mil-s-5626 spec.