

View Online at <https://aerobasegroup.com/nsn/5325-01-123-0948>

**Pinhole Diameter:**

Between 0.524 inches and 0.539 inches

**Fastener Style:**

Lock pin

**Length From Body Shoulder To Hole Center:**

1.310 inches

**Length From Body Hole Center To Body End:**

0.500 inches

**Stud Body Diameter:**

1.508 inches

**Fastener Stud Shank Length:**

4.710 inches

**Fastener Stud Shank Diameter:**

1.000 inches

**Special Features:**

Heat treat to 150-170 ksi per mil-h-6875; apply mil-g-7711 grease or vv-p-236 petrolatum on all threaded surfaces; 0.124 inch diameter hole 0.118 inch from end of threads

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626, 4140 cond d military specification single material response

**Surface Treatment:**

Cadmium post and paint post

**Surface Treatment Specification:**

Qq-p-416, type 2 cd 1 federal specification 1st treatment response post and mil-p-23377 military specification 2nd treatment response post and mil-c-22751 military specification 3rd treatment response post and mil-c-83286 military specification 4th treatment response post and mil-c-16173, grade 1 military specification 5th treatment response post

**Thread Size And Series/type Designator:**

1.000-12 unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A05400

**Mil-std (military Standard):**

Mil-s-5626 spec.