## NSN 5325-01-127-8898

Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5325-01-127-8898

Cross Sectional Shape:
Beveled one outside corner
Inside Diameter:
Between 0.967 inches and 0.992 inches
Casehardening Indicator:
Not casehardened
Minor Thickness:
Between 0.040 inches and 0.042 inches
Major Thickness:
Between 0.048 inches and 0.052 inches
Ring Style:
External
Usage Design:
External
Material Hardness Rating:
Between 47.0 rockwell c and 52.0 rockwell c
Material:
Steel, ams 5520
Material:
ivialeriai.
Steel comp 632
Steel comp 632
Steel comp 632  Material Specification:
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:  Passivated, qq-p-35
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:  Passivated, qq-p-35  Shelf Life:
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No
Steel comp 632  Material Specification:  Ams 5520 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Surface Treatment:  Passivated, qq-p-35  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: